Material Natural rubber from latex in compliance with ASTM D 1076

Packaging 1 Sterile Pair/Package - 50 Pairs/Dispenser Box - 4 Boxes/Case (200 Pairs/Case)

Product Numbers

SIZE (identified inside glove)	ASPN (Ansell Standard Product Number)
5 1/2	5711100
6	5711101
6 1/2	5711102
7	5711103
7 1/2	5711104
8	5711105
8 1/2	5711106
9	5711107

Dimensional Specifications (minimum length 276mm)

SIZE	Average Length mm (inches)	Average Palm Width mm (inches)
5 1/2	280 (11.0)	70 (2.8)
6	285 (11.2)	76 (3.0)
6 1/2	285 (11.2)	82 (3.2)
7	298 (11.7)	89 (3.5)
7 1/2	298 (11.7)	95 (3.7)
8	298 (11.7)	102 (4.0)
8 1/2	305 (12.0)	109 (4.3)
9	305 (12.0)	115 (4.5)

Thickness (single)

Color

Data from Sampling	Average Thickness
Fingertip, mm (mils)	0.23 (9.1)
Palm, mm (mils)	0.21 (8.3)
Cuff, mm (mils)	0.17 (6.5)

Physical Properties (ASTM, EN, and ISO Requirements)

	Before Aging	After Aging
Freedom from Holes (inspection level I)	1.5 AQL*	N/A
Tensile, MPa (p.s.i.) minimum	24 (3,480)	18 (2,610)
Elongation (%) minimum	750	560
Modulus, MPa (p.s.i.) maximum	5.5 (800)	N/A

Ansell manufacturing specifications meet or exceed all the above.

White

Accelerators

Zinc diethyldithiocarbamate (ZDEC)

Donning Agent

Residual
Powder Content

Certification

Manufacturing facility registered to ISO 9001, ISO 13485, and EN 46001
Contains 60 micrograms or less of total water-extractable protein per gram per glove

Quality Control

Sterilization

Challity Assessment and (CAL) 1/1/1000 000

Sterility Assurance Level (SAL) 1/1,000,000

References ANSI/ASQC Z1.4 Sampling Procedures and

Tables for Inspection by Attributes

Country of Origin | Sri Lanka

Storage Cool, dry environment, shielded from ozone and UV light



For additional information and samples, call Ansell Healthcare at 800-952-9916 or visit us at www.ansellhealthcare.com

Ansell Healthcare Products LLC I ansellhealthcare.com 200 Schulz Drive I Red Bank, NJ 07701 U.S.A. I Phone: (800) 952-9916 (U.S.A. only) Ansell, Perry and Style 42 are trademarks owned by Ansell Healthcare Products LLC or one of its affiliates. © 2007 All Rights Reserved.



^{*} Acceptable Quality Level – maximum % of gloves with defects

Except for applicable ASTM requirements, the above information
represents typical data for the product and should not be construed
or used as an actual product performance specification.